

Power Supply Unit type AC/DC Converter

L7SA-S

+30V/55W, +12V/65W, +5.5V/30W

HIGHLIGHTS

- Modular design for accommodating small size applications and easy maintenance
- Plug and play
- Isolated Output
- Natural air convection cooling
- Application : SPRINT LTE Pico



GENERAL SPECIFICATIONS

INPUT

- Voltage 1 ϕ AC 120/240VAC
- Efficiency \geq Typically 81%

OUTPUT

- Nominal output(Ch1) +30V/55W
- Nominal output(Ch2) +12V/65W
- Nominal output(Ch3) +5.5V/30W
- Ripple & Noise \leq 300/120/50mVp-p
(20MB/W SCOING)

ENVIRONMENT

- Operating Temperature -40 $^{\circ}$ C ~ +100 $^{\circ}$ C
- Operating Relative Humidity 5% ~ 95%
- Storage Temperature -40 $^{\circ}$ C ~ +85 $^{\circ}$ C
- Storage Relative Humidity 5% ~ 95%

FUNCTION

- Input Low · High Voltage Protection
- Output Over Voltage Protection
- Output Over Current Protection(at Load 110~130%)
- Output Short Protection
- Load Sharing (\pm 5%)
- Remote Feed Back

PHYSICAL DIMENSINS(W×D×H)

- 210 × 142 × 40 (mm)

AGENCY COMPLIANCE

- Standard – IEC CISPR Pub22 Class A
FCC Part15 Class A
- UL

